


NOTES:

- 1) EFFECTIVE LENGTH OF SECTION: 35.8 INCHES.
- 2) EFFECTIVE WIDTH OF SECTION: 20.0 INCHES.
- 3) EFFECTIVE HEIGHT OF SECTION: 3.08 INCHES.
- 4) CABLE CAPACITY: THREE 2.25"x2.22" CHANNELS.
- 5) WEIGHT: 29.5 LBS + BOX.
- 6) MATERIAL: UV STABILIZED POLYURETHANE YELLOW BASE AND BLUE LID.
- 7) TEMPERATURE RANGE: -40F TO +120F.
- 8) LOAD RATING: 25,000 POUNDS PER TIRE, 50,000 POUNDS PER AXLE AT 70F.
- 9) PACKAGING: UNIT SHIPS IN CARTON C8018256.
- 10) ONE C8020577 INSTRUCTION SHEET INSIDE THE CARTON.



REV	REVISION DESCRIPTION	DATE	BY	CHKD	ECN NO.
A	INITIAL DESIGN				

TOLERANCES
 FRAC. ± 1/64
 .X ± .015
 .XX ± .010
 .XXX ± .005
 ANGLES ± 1'
UNLESS OTHERWISE SPECIFIED
DO NOT SCALE
 B SIZE

DWG. APPROVALS DATE REV.
 _____ _____ _____
 _____ _____ _____
 DRAWN JRA 2/4/16
 CHK'D _____

ERICSON
 SAFETY IS OUR STANDARD
 ERICSON MANUFACTURING COMPANY
 1-800-ERICSON • www.ericson.com

DWG. TITLE		
CP3 ED SERIES PROTECTOR		
CP3-36-ED, 3 CHANNEL		
WITH ERICSON LOGO IN 2 PLACES		
SCALE NTS	PROJ NO. --/--	SHEET 1 OF 1
DWG. UNIT NO.		REV
CP3-36-ED		A