

# Perma-Spec Commercial/Industrial Grade Plugs and Connectors

Portable Power



## PERMA SPEC



### Industry Leading Features:

- cULus Approvals
- Durable Nylon Husk and Plug Module
- Husk Grooves for secure non-slipping gloved grip
- Two-Screw Internal Module design speeds assembly
- Floating Cord Clamp reduces cable jacket strain and resists cable pull-out
- Removable Cord Clamp insert allow a wide range of cable diameters.
- Cord clamp easily accommodates Wire-Mesh, I-Grip Design

 **Industry Leading, Ericson Exclusive**

### Locking Configurations:



15-AMP Locking  
EL515C, EL515P



20-AMP Locking  
EL520C, EL520P


### Unique Features:



Sturdy Nylon Husk  
and Face Module



Two Screw Face  
Module Speeds  
Assembly



Power Indicating  
Illuminated Plug and  
Connector




Floating Cord Clamp  
with Removable  
Cable Insert

# NEMA Configuration Cross Reference:

	Face View	NEMA Configuration	Amperage	Voltage	Perma-Spec Plug	Competitor H&L	Perma-Spec Connector	Competitor H&L
2-Pole / 3-Wire		NEMA 5-15	15A	125V	E515P	5266C	E515C	5269C
		NEMA 5-15	15A	125V	E515PL	5266C	E515CL	5269C
		NEMA 5-20	20A	125V	E520P	5366C	E520C	5369C
		NEMA L5-15	15A	125V	EL515P	4720-C	EL515C	4729C
		NEMA L5-20	20A	125V	EL520P	2311	EL520C	2313
		NEMA L5-30	30A	125V	EL530P	2611	EL530C	2613
		NEMA L7-15	15A	277V	EL715P	4770-C	EL715C	4779-C
		NEMA L7-20	20A	277V	EL720P	2331	EL720C	2333





## Wire Mesh Strain Relief

Part Number	Size Range (in)	Mesh Length (in)	Eye Opening (in)	Approx. Breaking Strength (lbs)
I-030	0.30 - 0.43	4.5	0.32	180
I-040	0.40 - 0.56	5	0.32	180
I-052	0.52 - 0.73	7	0.32	450







## Product Dimensions:

### 15-20-Amp Straight Blade & 15-Amp Locking



### 20-30-Amp Locking



## Related Products:

Click on an image or scan the QR code for more product information.

Learn More



[Perma-Link](#)  
[1510-P, 1610-C](#)



[Perma-Grip](#)  
[1510-PG, 1610-CG](#)



[Hospital Grade](#)  
[1530 PH, 1630 CH](#)



[SmartMonitor](#)  
[AEGCP Compliant](#)  
[1510-PML/GML, 1610-CML/GML](#)



[SmartMonitor](#)  
[AEGCP Compliant](#)  
[1510-PW6PL, 1610-CW6PL](#)



[Perma-Tite](#)  
[IP69k Water Tight](#)  
[1510-PW6P, 1610-CW6P](#)



[Perma-Kleen Antimicrobial](#)  
[IP69k Water Tight](#)  
[1510 PW6P-AM, 1610 CW6P-AM](#)



[Perma-Link 50A](#)  
[CS 6365-P, CS 6364-C](#)

## Factory & Custom Assembled Cordsets:

Click on an image or scan the QR code for more product information.



[Perma-Link Cordset](#)



[Perma-Tite Cordset](#)



[Perma-Kleen Cordset](#)



[SmartMonitor Cordset](#)



**ERICSON**  
SAFETY IS OUR STANDARD

Ericson Manufacturing Company  
4323 Hamann Parkway  
Willoughby, OH 44094, USA



1-800-ERICSON  
info@ericson.com  
L1000878C